

TECHNICAL SPECIFICATIONS

- 300mm LED Flashers on Top board + 4 corners lower board
- 200mm LED Light Arrow (Left, Right, Cross)
- Wired control in Cabin for TMA + Arrow Board
- Hydraulic moveable 211 Sign 1500mm (Left, Right, Down)
- Hydraulic Vertical Lift for Top Arrow Board
- Dimensions 2300mm x 2500mm


ABOUT THE VD-SL230

The VDSL-230 arrow boards are commonly used in the UK, UAE, Qatar and the GCC region. This arrow board can be controlled with the Verdegro combined TMA and arrow board wired controller when purchased as a complete set utilizing the hydraulics of the TMA. The handheld controller can lower and raise the TMA as well as functions, left arrow, right arrow and cross on the arrow board. Additionally, it has 3 extra function buttons that can be used, for example, to activate work lights or additional flashers, allowing the operator to use only one controller and remain focused on the job. Optionally it can also be purchased as a standalone arrow board mounted on the truck instead of directly on the TMA with a separate hydraulic powerpack that can be ordered when used as standalone system.

60 Verdegro catalogus

Table of contents and dimensions	
Transport height	2113 mm / 6,9 ft
Installation length	3113 mm / 10,2 ft
Width	2300 mm / 7,5 ft
Weight complete installation	Approx. 450 kg / 990 lbs

Note: all these dimensions are approximately, no rights can be derived.





Crash 61