



The VD-SL230 is named this way because the width of the arrow board is the 2300 mm version.

VD-SL230

TECHNICAL SPECIFICATIONS

- 300 mm LED flashers on top board and on all four corners of the lower board
- 200 mm LED light arrow (Left, Right, Cross)
- Wired in-cabin control for TMA and arrow board
- Hydraulically movable 211 Sign, 1500 mm (Left, Right, Down)
- Hydraulic vertical lift for top arrow board

ABOUT THE VD-SL230

The VD-SL230 arrow board is a reliable and versatile system, widely used in the UAE, Qatar, and across the GCC region. It provides excellent visibility and easy operation for safe and efficient traffic management.

When used with the Verdegro TMA, the VD-SL230 can be operated through the combined wired controller, allowing the user to raise or lower the TMA and select Left Arrow, Right Arrow, or Cross modes.

The handheld controller also includes three extra buttons that can be used for additional functions such as work lights or extra flashers. This means the operator can control everything from one unit while staying focused on the job.

The VD-SL230 is also available as a standalone arrow board, mounted directly on the truck instead of the TMA. In this configuration, it can be equipped with a separate hydraulic power pack, making it an ideal solution for a wide range of vehicle types and operational needs.

Table of contents and dimensions

Transport height	2113 mm / 6,9 ft
Installation length	3113 mm / 10,2 ft
Width	2300 mm / 7,5 ft
Weight complete installation	Approx. 450 kg / 990 lbs

Note: all these dimensions are approximately, no rights can be derived.

VD-SL230 ARROW BOARD

